



NAVE series	
PRODUCT SPECIFICATIONS	
Conformity to Standards:	specific UNAV standards
Protection rating:	IP66
Impact resistance:	> IK 10
Temperature resistance:	Operating: -40°C - +70°C Storage: -50°C - +80°C
Casing:	Painted solid brass



**NAVE SERIES**  
Watertight UNAV 1436 interlocked socket-outlets in brass enclosure painted marine grey, with cable glands UNAV 1948 IP56

Rated current (A)	Rated voltage	Poles	Cable gland No.	Palazzoli Code	Pack Q.ty
10	127V~	2P+≋	1	462151	1
	230V~	2P+≋	1	462131	1

**Equipment:**  
brass cable glands M24x1,5. Earth screws inside and outside the box.



**NAVE SERIES**  
Watertight UNAV 1437 plugs with ring-nut and rubber protection sleeve IP56

Rated current (A)	Rated voltage	Poles	Palazzoli Code	Pack Q.ty
10	24V~	2P+≋	467021	10
	127V~	2P+≋	467051	10
	230V~	2P+≋	467031	10



**NAVE SERIES**  
Watertight UNAV 2169 socket-outlets in brass enclosure painted marine grey, with switch, for supply to refrigerated containers IP66

Rated current (A)	Frequency	Rated voltage	Poles	H Ref.	No. of entries	Entry type	Palazzoli Code	Pack Q.ty
32	50/60Hz	380/440V	3P+≋	3	1	30x18 M30x2 UNAV 1948	472401	1
	50/60Hz	380/440V	3P+≋	3	2 opposite side	1" gas	472411	1

**Equipment:**  
brass cable glands. 3x16 mm<sup>2</sup> terminal block on ceramic support.

**Characteristics:**  
switch is controlled directly by inserting/removing the plug.

**Uses:**  
on board container ships and ferries, in container warehouses and maritime, naval, railway terminals, etc.



**NAVE SERIES**  
Watertight screwcaps with gasket for UNAV 2169 socket-outlet entries IP66

Thread	Manufactured material	Palazzoli Code	Pack Q.ty
1" gas	brass	472901	10



**NAVE SERIES**  
UNAV 2172 watertight plug in painted marine grey brass IP66

Rated current (A)	Frequency	Rated voltage	Voltage colour	Poles	H Ref.	Palazzoli Code	Pack Q.ty
32	50/60Hz	380/440V	●	3P+≋	3	477411	2

**Equipment:**  
UNAV 1948 36x21 cable gland.

**Uses:**  
for refrigerated containers power supply.