



IP66/ ZONE 2/21, 22

## BORDER-N-LED-M598

Order number	Name	Lighting fixture luminous flux (lm)	Power input (W)	Rated power output (lm/W)	Ta (°C)	Dimensions of lighting fixture A x B x C (mm)	Weight (kg)
<b>SQ</b>							
080670	BORDER-N-LED-2/21-M598-SQ-GLM-3300-4K, IP66	2688	17	158	-20°C/60°C	598x598x87	10,5
080671	BORDER-N-LED-2/21-M598-SQ-GLM-4800-4K, IP66	3978	27	147	-20°C/60°C	598x598x87	10,5
080672	BORDER-N-LED-2/21-M598-SQ-GLM-6300-4K, IP66	5237	37	142	-20°C/60°C	598x598x87	10,5
080673	BORDER-N-LED-2/21-M598-SQ-GLM-7200-4K, IP66	6067	41	148	-20°C/60°C	598x598x87	10,5
080674	BORDER-N-LED-2/21-M598-SQ-GLM-8700-4K, IP66	7277	49	149	-20°C/60°C	598x598x87	10,5
080675	BORDER-N-LED-2/21-M598-SQ-GLM-12000-4K, IP66	9996	70	143	-20°C/45°C	598x598x87	10,5
<b>SQ-FROST</b>							
081420	BORDER-N-LED-2/21-M598-FROST-SQ-GLM-3300-4K, IP66	2688	17	158	-40°C/55°C	598x598x87	10,5
081421	BORDER-N-LED-2/21-M598-FROST-SQ-GLM-4800-4K, IP66	3978	27	147	-40°C/55°C	598x598x87	10,5
081422	BORDER-N-LED-2/21-M598-FROST-SQ-GLM-6300-4K, IP66	5237	37	142	-40°C/55°C	598x598x87	10,5
081423	BORDER-N-LED-2/21-M598-FROST-SQ-GLM-7200-4K, IP66	6067	41	148	-40°C/60°C	598x598x87	10,5
081424	BORDER-N-LED-2/21-M598-FROST-SQ-GLM-8700-4K, IP66	7277	49	149	-40°C/60°C	598x598x87	10,5
<b>R</b>							
080700	BORDER-N-LED-2/21-M598-R-GLM-3300-4K, IP66	2630	17	155	-20°C/60°C	1198x298x87	11,5
080701	BORDER-N-LED-2/21-M598-R-GLM-4800-4K, IP66	3906	27	145	-20°C/60°C	1198x298x87	11,5
080702	BORDER-N-LED-2/21-M598-R-GLM-6300-4K, IP66	5143	37	139	-20°C/60°C	1198x298x87	11,5
080703	BORDER-N-LED-2/21-M598-R-GLM-7200-4K, IP66	5928	41	145	-20°C/60°C	1198x298x87	11,5
080704	BORDER-N-LED-2/21-M598-R-GLM-8700-4K, IP66	7077	49	144	-20°C/55°C	1198x298x87	11,5
080705	BORDER-N-LED-2/21-M598-R-GLM-12000-4K, IP66	9816	70	140	-20°C/45°C	1198x298x87	11,5
<b>R-FROST</b>							
081450	BORDER-N-LED-2/21-M598-FROST-R-GLM-3300-4K, IP66	2630	17	155	-40°C/60°C	1198x298x87	11,5
081451	BORDER-N-LED-2/21-M598-FROST-R-GLM-4800-4K, IP66	3906	27	145	-40°C/60°C	1198x298x87	11,5
081452	BORDER-N-LED-2/21-M598-FROST-R-GLM-6300-4K, IP66	5143	37	139	-40°C/60°C	1198x298x87	11,5
081453	BORDER-N-LED-2/21-M598-FROST-R-GLM-7200-4K, IP66	5928	41	145	-40°C/60°C	1198x298x87	11,5
081454	BORDER-N-LED-2/21-M598-FROST-R-GLM-8700-4K, IP66	7077	49	144	-40°C/60°C	1198x298x87	11,5
<b>SQ</b>							
080676	BORDER-N-LED-2/21-M598-SQ-OP-3300-4K, IP66	2372	17	140	-20°C/60°C	598x598x87	10,5
080677	BORDER-N-LED-2/21-M598-SQ-OP-4800-4K, IP66	3510	27	130	-20°C/60°C	598x598x87	10,5
080678	BORDER-N-LED-2/21-M598-SQ-OP-6300-4K, IP66	4621	37	125	-20°C/60°C	598x598x87	10,5
080679	BORDER-N-LED-2/21-M598-SQ-OP-7200-4K, IP66	5353	41	131	-20°C/60°C	598x598x87	10,5
080680	BORDER-N-LED-2/21-M598-SQ-OP-8700-4K, IP66	6420	49	131	-20°C/60°C	598x598x87	10,5
080681	BORDER-N-LED-2/21-M598-SQ-OP-12000-4K, IP66	8820	70	126	-20°C/45°C	598x598x87	10,5
<b>SQ-FROST</b>							
081426	BORDER-N-LED-2/21-M598-FROST-SQ-OP-3300-4K, IP66	2372	17	140	-40°C/55°C	598x598x87	10,5
081427	BORDER-N-LED-2/21-M598-FROST-SQ-OP-4800-4K, IP66	3510	27	130	-40°C/55°C	598x598x87	10,5
081428	BORDER-N-LED-2/21-M598-FROST-SQ-OP-6300-4K, IP66	4621	37	125	-40°C/55°C	598x598x87	10,5
081429	BORDER-N-LED-2/21-M598-FROST-SQ-OP-7200-4K, IP66	5353	41	131	-40°C/60°C	598x598x87	10,5
081430	BORDER-N-LED-2/21-M598-FROST-SQ-OP-8700-4K, IP66	6420	49	131	-40°C/60°C	598x598x87	10,5
<b>R</b>							
080706	BORDER-N-LED-2/21-M598-R-OP-3300-4K, IP66	2370	17	139	-20°C/60°C	1198x298x87	11,5
080707	BORDER-N-LED-2/21-M598-R-OP-4800-4K, IP66	3519	27	130	-20°C/60°C	1198x298x87	11,5
080708	BORDER-N-LED-2/21-M598-R-OP-6300-4K, IP66	4634	37	125	-20°C/60°C	1198x298x87	11,5
080709	BORDER-N-LED-2/21-M598-R-OP-7200-4K, IP66	5341	41	130	-20°C/60°C	1198x298x87	11,5
080710	BORDER-N-LED-2/21-M598-R-OP-8700-4K, IP66	6376	49	130	-20°C/55°C	1198x298x87	11,5
080711	BORDER-N-LED-2/21-M598-R-OP-12000-4K, IP66	8844	70	126	-20°C/55°C	1198x298x87	11,5
<b>R-FROST</b>							
081456	BORDER-N-LED-2/21-M598-FROST-R-OP-3300-4K, IP66	2370	17	139	-40°C/60°C	1198x298x87	11,5
081457	BORDER-N-LED-2/21-M598-FROST-R-OP-4800-4K, IP66	3519	27	130	-40°C/60°C	1198x298x87	11,5
081458	BORDER-N-LED-2/21-M598-FROST-R-OP-6300-4K, IP66	4634	37	125	-40°C/60°C	1198x298x87	11,5
081459	BORDER-N-LED-2/21-M598-FROST-R-OP-7200-4K, IP66	5341	41	130	-40°C/60°C	1198x298x87	11,5
081460	BORDER-N-LED-2/21-M598-FROST-R-OP-8700-4K, IP66	6376	49	130	-40°C/60°C	1198x298x87	11,5

Order number	Name	Lighting fixture luminous flux (lm)	Power input (W)	Rated power output (lm/W)	Ta (°C)	Dimensions of lighting fixture A x B x C (mm)	Weight (kg)
<b>SQ</b>							
080682	BORDER-N-LED-2/21-M598-SQ-MP-3300-4K, IP66	2359	17	139	-20°C/60°C	598x598x87	10,5
080683	BORDER-N-LED-2/21-M598-SQ-MP-4800-4K, IP66	3491	27	129	-20°C/60°C	598x598x87	10,5
080684	BORDER-N-LED-2/21-M598-SQ-MP-6300-4K, IP66	4596	37	124	-20°C/60°C	598x598x87	10,5
080685	BORDER-N-LED-2/21-M598-SQ-MP-7200-4K, IP66	5324	41	130	-20°C/60°C	598x598x87	10,5
080686	BORDER-N-LED-2/21-M598-SQ-MP-8700-4K, IP66	6386	49	130	-20°C/60°C	598x598x87	10,5
080687	BORDER-N-LED-2/21-M598-SQ-MP-12000-4K, IP66	8772	70	125	-20°C/45°C	598x598x87	10,5
<b>SQ-FROST</b>							
081432	BORDER-N-LED-2/21-M598-FROST-SQ-MP-3300-4K, IP66	2359	17	139	-40°C/55°C	598x598x87	10,5
081433	BORDER-N-LED-2/21-M598-FROST-SQ-MP-4800-4K, IP66	3491	27	129	-40°C/55°C	598x598x87	10,5
081434	BORDER-N-LED-2/21-M598-FROST-SQ-MP-6300-4K, IP66	4596	37	124	-40°C/55°C	598x598x87	10,5
081435	BORDER-N-LED-2/21-M598-FROST-SQ-MP-7200-4K, IP66	5324	41	130	-40°C/55°C	598x598x87	10,5
081436	BORDER-N-LED-2/21-M598-FROST-SQ-MP-8700-4K, IP66	6386	49	130	-40°C/55°C	598x598x87	10,5
<b>R</b>							
080712	BORDER-N-LED-2/21-M598-R-MP-3300-4K, IP66	2347	17	138	-20°C/60°C	1198x298x87	11,5
080713	BORDER-N-LED-2/21-M598-R-MP-4800-4K, IP66	3486	27	129	-20°C/60°C	1198x298x87	11,5
080714	BORDER-N-LED-2/21-M598-R-MP-6300-4K, IP66	4590	37	124	-20°C/60°C	1198x298x87	11,5
080715	BORDER-N-LED-2/21-M598-R-MP-7200-4K, IP66	5291	41	129	-20°C/60°C	1198x298x87	11,5
080716	BORDER-N-LED-2/21-M598-R-MP-8700-4K, IP66	6315	49	129	-20°C/60°C	1198x298x87	11,5
080717	BORDER-N-LED-2/21-M598-R-MP-12000-4K, IP66	8760	70	125	-20°C/60°C	1198x298x87	11,5
<b>R-FROST</b>							
081462	BORDER-N-LED-2/21-M598-FROST-R-MP-3300-4K, IP66	2347	17	138	-40°C/60°C	1198x298x87	11,5
081463	BORDER-N-LED-2/21-M598-FROST-R-MP-4800-4K, IP66	3486	27	129	-40°C/60°C	1198x298x87	11,5
081464	BORDER-N-LED-2/21-M598-FROST-R-MP-6300-4K, IP66	4590	37	124	-40°C/60°C	1198x298x87	11,5
081465	BORDER-N-LED-2/21-M598-FROST-R-MP-7200-4K, IP66	5291	41	129	-40°C/60°C	1198x298x87	11,5
081466	BORDER-N-LED-2/21-M598-FROST-R-MP-8700-4K, IP66	6315	49	129	-40°C/60°C	1198x298x87	11,5

Order number	Name	Lighting fixture luminous flux (lm)	Power input (W)	Rated power output (lm/W)	Ta (°C)	Dimensions of lighting fixture A x B x C (mm)	Weight (kg)
<b>SQ</b>							
080688	BORDER-N-LED-2/21-M598-SQ-CGOP-3300-4K, IP66	2459	17	145	-20°C/60°C	598x598x87	10,5
080689	BORDER-N-LED-2/21-M598-SQ-CGOP-4800-4K, IP66	3639	27	135	-20°C/60°C	598x598x87	10,5
080690	BORDER-N-LED-2/21-M598-SQ-CGOP-6300-4K, IP66	4791	37	129	-20°C/60°C	598x598x87	10,5
080691	BORDER-N-LED-2/21-M598-SQ-CGOP-7200-4K, IP66	5550	41	135	-20°C/60°C	598x598x87	10,5
080692	BORDER-N-LED-2/21-M598-SQ-CGOP-8700-4K, IP66	6656	49	136	-20°C/60°C	598x598x87	10,5
080693	BORDER-N-LED-2/21-M598-SQ-CGOP-12000-4K, IP66	9144	70	131	-20°C/45°C	598x598x87	10,5
<b>SQ-FROST</b>							
081438	BORDER-N-LED-2/21-M598-FROST-SQ-CGOP-3300-4K, IP66	2459	17	145	-40°C/55°C	598x598x87	10,5
081439	BORDER-N-LED-2/21-M598-FROST-SQ-CGOP-4800-4K, IP66	3639	27	135	-40°C/55°C	598x598x87	10,5
081440	BORDER-N-LED-2/21-M598-FROST-SQ-CGOP-6300-4K, IP66	4791	37	129	-40°C/55°C	598x598x87	10,5
081441	BORDER-N-LED-2/21-M598-FROST-SQ-CGOP-7200-4K, IP66	5550	41	135	-40°C/60°C	598x598x87	10,5
081442	BORDER-N-LED-2/21-M598-FROST-SQ-CGOP-8700-4K, IP66	6656	49	136	-40°C/60°C	598x598x87	10,5
<b>R</b>							
080718	BORDER-N-LED-2/21-M598-R-CGOP-3300-4K, IP66	2321	17	137	-20°C/60°C	1198x298x87	11,5
080719	BORDER-N-LED-2/21-M598-R-CGOP-4800-4K, IP66	3462	27	128	-20°C/60°C	1198x298x87	11,5
080720	BORDER-N-LED-2/21-M598-R-CGOP-6300-4K, IP66	4558	37	123	-20°C/60°C	1198x298x87	11,5
080721	BORDER-N-LED-2/21-M598-R-CGOP-7200-4K, IP66	5254	41	128	-20°C/60°C	1198x298x87	11,5
080722	BORDER-N-LED-2/21-M598-R-CGOP-8700-4K, IP66	6272	49	128	-20°C/55°C	1198x298x87	11,5
080723	BORDER-N-LED-2/21-M598-R-CGOP-12000-4K, IP66	8700	70	124	-20°C/40°C	1198x298x87	11,5
<b>R-FROST</b>							
081468	BORDER-N-LED-2/21-M598-FROST-R-CGOP-3300-4K, IP66	2331	17	137	-40°C/60°C	1198x298x87	11,5
081469	BORDER-N-LED-2/21-M598-FROST-R-CGOP-4800-4K, IP66	3462	27	128	-40°C/60°C	1198x298x87	11,5
081470	BORDER-N-LED-2/21-M598-FROST-R-CGOP-6300-4K, IP66	4558	37	123	-40°C/60°C	1198x298x87	11,5
081471	BORDER-N-LED-2/21-M598-FROST-R-CGOP-7200-4K, IP66	5254	41	128	-40°C/60°C	1198x298x87	11,5
081472	BORDER-N-LED-2/21-M598-FROST-R-CGOP-8700-4K, IP66	6272	49	128	-40°C/60°C	1198x298x87	11,5

Order number	Name	Lighting fixture luminous flux (lm)	Power input (W)	Rated power output (lm/W)	Ta (°C)	Dimensions of lighting fixture A x B x C (mm)	Weight (kg)
<b>SQ</b>							
080694	BORDER-N-LED-2/21-M598-SQ-CGMP-3300-4K, IP66	2440	17	144	-20°C/60°C	598x598x87	10,5
080695	BORDER-N-LED-2/21-M598-SQ-CGMP-4800-4K, IP66	3610	27	134	-20°C/60°C	598x598x87	10,5
080696	BORDER-N-LED-2/21-M598-SQ-CGMP-6300-4K, IP66	4753	37	128	-20°C/60°C	598x598x87	10,5
080697	BORDER-N-LED-2/21-M598-SQ-CGMP-7200-4K, IP66	5506	41	134	-20°C/60°C	598x598x87	10,5
080698	BORDER-N-LED-2/21-M598-SQ-CGMP-8700-4K, IP66	6604	49	135	-20°C/60°C	598x598x87	10,5
080699	BORDER-N-LED-2/21-M598-SQ-CGMP-12000-4K, IP66	9072	70	130	-20°C/45°C	598x598x87	10,5
<b>SQ-FROST</b>							
081444	BORDER-N-LED-2/21-M598-FROST-SQ-CGMP-3300-4K, IP66	2440	17	144	-40°C/55°C	598x598x87	10,15
081445	BORDER-N-LED-2/21-M598-FROST-SQ-CGMP-4800-4K, IP66	3610	27	134	-40°C/55°C	598x598x87	10,15
081446	BORDER-N-LED-2/21-M598-FROST-SQ-CGMP-6300-4K, IP66	4753	37	128	-40°C/55°C	598x598x87	10,15
081447	BORDER-N-LED-2/21-M598-FROST-SQ-CGMP-7200-4K, IP66	5506	41	134	-40°C/60°C	598x598x87	10,15
081448	BORDER-N-LED-2/21-M598-FROST-SQ-CGMP-8700-4K, IP66	6604	49	135	-40°C/60°C	598x598x87	10,15
<b>R</b>							
080724	BORDER-N-LED-2/21-M598-R-CGMP-3300-4K, IP66	2360	17	139	-20°C/60°C	1198x298x87	11,5
080725	BORDER-N-LED-2/21-M598-R-CGMP-4800-4K, IP66	3505	27	130	-20°C/60°C	1198x298x87	11,5
080726	BORDER-N-LED-2/21-M598-R-CGMP-6300-4K, IP66	4615	37	125	-20°C/60°C	1198x298x87	11,5
080727	BORDER-N-LED-2/21-M598-R-CGMP-7200-4K, IP66	5320	41	130	-20°C/60°C	1198x298x87	11,5
080728	BORDER-N-LED-2/21-M598-R-CGMP-8700-4K, IP66	6350	49	130	-20°C/55°C	1198x298x87	11,5
080729	BORDER-N-LED-2/21-M598-R-CGMP-12000-4K, IP66	8808	70	126	-20°C/45°C	1198x298x87	11,5
<b>R-FROST</b>							
081474	BORDER-N-LED-2/21-M598-FROST-R-CGMP-3300-4K, IP66	2360	17	139	-40°C/60°C	1198x298x87	11,5
081475	BORDER-N-LED-2/21-M598-FROST-R-CGMP-4800-4K, IP66	3505	27	130	-40°C/60°C	1198x298x87	11,5
081476	BORDER-N-LED-2/21-M598-FROST-R-CGMP-6300-4K, IP66	4615	37	125	-40°C/60°C	1198x298x87	11,5
081477	BORDER-N-LED-2/21-M598-FROST-R-CGMP-7200-4K, IP66	5320	41	130	-40°C/60°C	1198x298x87	11,5
081478	BORDER-N-LED-2/21-M598-FROST-R-CGMP-8700-4K, IP66	6350	49	130	-40°C/60°C	1198x298x87	11,5

