



IP 66 / zone 1/21

EXTEND-Ex-P-LED

Order number	Name	Lighting fixture luminous flux (lm)	Power input (W)	Rated power output (lm/W)	Ta max (°C)	Dimensions of lighting fixture A x B x C (mm)	Mounting spacing D (mm)	Equivalent**	Weight (kg)
053275	EXTEND-Ex-P-LED-D-2750-218-4K	2224	16	139	55*	728x244x156	570	1x36W/2x18W	5,06
053260	EXTEND-Ex-P-LED-D-4000-218-4K	3158	28	113	55	728x244x156	570	X	5,06
053276	EXTEND-Ex-P-LED-D-5500-236-4K	4123	30	137	55	1328x244x156	830	2x36W	8,1
053261	EXTEND-Ex-P-LED-D-8000-236-4K	6138	53	116	55*	1328x244x156	830	X	8,1
053277	EXTEND-Ex-P-LED-WOD-2750-218-4K	2224	16	139	55*	728x244x156	570	1x36W/2x18W	4,98
053262	EXTEND-Ex-P-LED-WOD-4000-218-4K	3158	28	113	55	728x244x156	570	X	4,98
053278	EXTEND-Ex-P-LED-WOD-5500-236-4K	4123	30	137	55	1328x244x156	830	2x36W	7,94
053263	EXTEND-Ex-P-LED-WOD-8000-236-4K	6138	53	116	55*	1328x244x156	830	X	7,94

