



IP 66 / ZONE 2/22

## SALUKA-N-LED

Order number	Name	Lighting fixture luminous flux (lm)	Power input (W)	Rated power outpt (lm/W)	Ta max (°C)	Dimensions of lighting fixture A x B x C (mm)	Mounting spacing D (mm)	Weight (kg)
080000	SALUKA-N-LED-OP-1250-218-G2-4K	1155	8	145	45	705x192x90	510	3,8
080001	SALUKA-N-LED-OP-2500-218-G2-4K	2220	15	148	60	705x192x90	510	3,8
080002	SALUKA-N-LED-OP-5000-218-G2-4K	4409	29	153	55	705x192x90	510	3,9
080003	SALUKA-N-LED-OP-2500-236-G2-4K	2220	15	148	60	1305x192x90	1110	7,1
080004	SALUKA-N-LED-OP-5000-236-G2-4K	4440	29	154	60	1305x192x90	1110	7,1
080005	SALUKA-N-LED-OP-10000-236-G2-4K	8819	58	153	50	1305x192x90	1410	7,2
080006	SALUKA-N-LED-OP-3750-258-G2-4K	3330	22	152	55	1605x192x90	1410	8,1
080007	SALUKA-N-LED-OP-3750-258-G2-4K	6661	44	152	55	1605x192x90	1410	8,1
080008	SALUKA-N-LED-OP-12550-258-G2-4K	11305	74	153	45	1605x192x90	1410	8,3
080009	SALUKA-N-LED-OP-16700-258-G2-4K	14175	95	150	50	1605x192x90	1410	8,5
080010	SALUKA-N-LED-OP-20000-258-G2-4K	16963	117	145	45	1605x192x90	1410	8,5

